THIS DOCUMENT IS THE PROPERTY OF SELECT CONTROLS INCORPOPARTED AND IS CONNEYED WITH THE EXPRESS CONDITION THAT IT AND THE INFORMATION CONTAINED IN IT ARE NOT TO BE USED, DISCLOSED, OR REPRODUCED IN WHOLE OR IN PART, FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF SELECT CONTROLS INCORPORATED; AND THAT IN OR GIGHT IS GRANTED TO DISCLOSE OR ORATED; AND THAT IN ORIGIN IS ORD DISCLOSE OF THE ORIGINAL PROPERTY ORIGINAL PROPERTY OF THE ORIGI .7 ù 9 œ 9 4. بې 1. WEIGHT: 1.85 GRAMS MAXIMUM CONTACTS: SPST, NORMALLY OPEN, MOMENTARY VIBRATION-CONTACT RATING: CONTINUOUS DUTY- 200 MILLIAMPERES DELAY— UPON APPLICATION OF 12.5 g'S ,HALF—SINE INPUT OF 15 MILLISECOND DURATION, SWITCH CONTACTS SHALL CLOSE WITHIN 15 MILLISECONDS OF PEAK g AMPLITUDE. UNIT IS HERMETICALLY SEALED WITH 90% GN2 INSULATION RESISTANCE: INSULATED LEAD TO CASE, SWITCH CLOSURE: SWITCH SHALL CLOSE CONTACTS, CONTACT RESISTANCE 2.0 OHMS MAX. AT 8.0 +/- 0.7g WHEN TESTED AT ROOM TEMPERATURE WITH SLOWLY INCREASING ACCELERATION APPLIED.(CENTRIFUGE TEST) AND 10% He FILL OPERATING TEMPERATURE RANGE: -65°F TO +185°F CONTACT, CASE GROUND. SWITCH SHALL NEITHER BE DAMAGED NOR BE ACTIVATED WHEN EXPOSED TO VIBRATION PER MIL—STD—202F, METHOD 214A,TEST CONDITION A (5.35 G RMS) INTERMITTENT DUTY- 1.0 AMPERES AT 28 VDC RESISTIVE LOAD AT 28 VDC RESISTIVE LOAD 200 MEGOHMS MIN. AT 500 VDC DO NOT SOLLE DRAWING
REMOYE BURRS, BREW, SHAPP EDGES,
TOLERANCE UNLESS SPECIFIED:
PRACT: ±1/64
MCH FINISH:
RMS
RMS
RMS
ANGLE ±0°30°
RMS (X.XX) MATERIAL ø.191 MAX. DENOTES DIMENSIONS HS S Z MILLIMETERS SURFACE ANGLE ±0"30"
DEC: .00 ± .010
DEC: .000 ±.005 DIRECTION TO CLOSE CONTACTS ACCELERATE IN THIS 3090-3-000 030 MAX. 422 MAX. 桑 R S S N/A REO'o NORMALLY OPEN, 8.0g ACCELERATION SWITCH 70 P PART NO. Z X ₽ — 2X .50 MIN. SOULE: 4:1 NOTED 四日 OF MATERIAL .105 .095 eontrols inc. ₹ DESCRIPTION DESCRIPTION ø.016-.019 CASE GROUND LEAD WITH Ø.040 MAX. BY .013 MAX. HIGH BUTT WELD REVISIONS WITH .014 MAX. GLASS Ø.016-.019 INSULATED LEAD BOHEMIA, N.Y. 45-3 KNICKERBOCKER SHEET 1 OF 1 3090-3-000 ø.218 MAX 孯 REMARKS 웆 S